

Focused on delivering superior products at a high value.



Teel BQ Purple Mono SDR 9 / 11 PP-RCT pipe is colored coded purple, available from 1/2" (20mm) through 10" (250mm). The Teel Purple BQ Mono SDR 9 / 11 pipe is used for reclaimed water applications. Pressure rating: 280 PSI at 68°F, 115 PSI at 140°F. Listings and certificates: ASTM F2389, NSF/ANSI-14, CSA B137.11, ICC-ES.



DESCRIPTION	SDR	PART NUMBER	NOM. O.D. - O.D.
1/2" (20mm) x 19 feet	9	C02009L	1/2" 20 x 2.3mm
3/4" (25mm) x 19 feet	9	C02509L	3/4" 25 x 2.8mm
1" (32mm) x 19 feet	11	C03211L	1" 32 x 2.9mm
1-1/4" (40mm) x 19 feet	11	C04011L	1-1/4" 40 x 3.7mm
1-1/2" (50mm) x 19 feet	11	C05011L	1-1/2" 50 x 4.6mm
2" (63mm) x 19 feet	11	C06311L	2" 63 x 5.8mm
2-1/2" (75mm) x 19 feet	11	C07511L	2-1/2" 75 x 6.8mm
3" (90mm) x 19 feet	11	C09011L	3" 90 x 8.2mm
3-1/2" (110mm) x 19 feet	11	C11011L	3-1/2" 110 x 10.0mm
4" (125mm) x 19 feet	11	C12511L	4" 125 x 11.4mm
6" (160mm) x 19 feet	11	C16011L	6" 160 x 14.6mm
8" (200mm) x 19 feet	11	C20011L	8" 200 x 18.2mm
10" (250mm) x 19 feet	11	C25011L	10" 250 x 22.7mm

Advantages of TeelBQ Composite Piping

- 100% Recyclable
- High Resistance to Chemicals
- High Pressure Tolerances and Ratings
- High Flow Rates
- Noise Reduction
- Light Weight
- Speed and Ease of Fusion Technology
- Rust and Corrosion Resistant

Contact us today for more information.

(608) 355-3080
sales@TeelBQ.com
www.TeelBQAmericas.com



Purple Mono PP-RCT Pipe

Teel BQ Purple Mono SDR 9 & 11 PP-RCT pipes are manufactured from high quality, Polypropylene Random Co-polymer resins (PP-RCT). Its physical and chemical properties make Teel Purple BQ Mono PP-RCT a versatile piping system in a wide range of applications. The Teel BQ Purple Mono SDR 9 / 11 piping system is designed for rainwater, gray water and reclaimed water applications.



NOMINAL OD	METRIC OD (mm)	SDR 7.4 (gpm)	SDR 9 (gpm)	SDR 11 (gpm)	SDR 17.6 (gpm)
1/2"	20	6.3	7.2		
3/4"	25	9.8	11.4		
1"	32	16.3	18.7	20.8	
1-1/4"	40	25.5	29.2	32.3	
1-1/2"	50	39.8	45.7	50.5	
2"	63	63.7	72.3	80.2	
2-1/2"	75	89.8	102.8	114.4	
3"	90	129.8	147.8	164.4	
3-1/2"	110	193.3	221.3	245.9	
4"	125	250.3	285.5	317.0	372.5
6"	160	409.8	468.0	519.3	610.0
8"	200	639.6	730.8	812.0	952.7
10"	250	1000.6	1144.2	1270.0	1489.9
12"	315	1588.3		2016.4	2365.0
14"	355	2019.5		2562.1	3006.6
16"	400			3252.1	3814.9
18"	450			4113.2	4830.1
20"	500				5959.5
22"	560				7482.1
24"	630				9467.0

* Flow Rates, based on a velocity of 8 feet per second.

PIPE	LENGTH	10°F	20°F	30°F	40°F	50°F	60°F	80°F	100°F
Linear expansion co-efficient for TeelBQ Mono pipe is: 0.150mm / mK = 1.008 x 10.3" / ft °F									
Mono	10'	0.1"	0.2"	0.3"	0.4"	0.5"	0.6"	0.8"	1.0"
Mono	30'	0.3"	0.6"	0.9"	1.2"	1.5"	1.8"	2.4"	3.0"
Mono	100'	1.0"	2.0"	3.0"	4.0"	5.0"	6.0"	8.0"	10.0"
Linear expansion co-efficient for TeelBQ Composite pipe is: 0.0350mm / mK = 2.367 x 10.4" / ft °F									
Composite	10'	0.0"	0.0"	0.1"	0.1"	0.1"	0.1"	0.2"	0.2"
Composite	30'	0.1"	0.1"	0.2"	0.3"	0.3"	0.4"	0.5"	0.7"
Composite	100'	0.2"	0.5"	0.7"	0.9"	1.1"	1.4"	1.8"	2.3"

* Temperature in chart represents the difference between operating temperature - room temperature.

Photographs of product shown in this publication are used for representational purposes only. All data and specifications are subject to change without notification.

Literature_purple_SDR11_030419



(608) 355-3080
 sales@TeelBQ.com
 www.TeelBQAmericas.com